

SPECIFICATIONS – Delta Q QuiQ Battery Charger

Model	24 Volt / 25 amps QuiQ Charger	36 Volt / 21 amps QuiQ Charger	48 Volt / 18 amps QuiQ Charger	72 Volt / 12 amps QuiQ Charger	96 Volt / 10 amps QuiQ Charger
Enerdrive Code	912-2400	912-3600	912-4800	912-7200	912-9600
Output Current (nominal)	25amps	21amps	18amps	12amps	10amps
Output Voltage (nominal)	24 Vdc	36Vdc	36 Vdc	72 Vdc	96 Vdc
DC Output Connections	1				
AC Input Voltage / Frequency	85 – 265 Vac, 45 – 65 Hz				
Temperature Compensation	Via Temp Sensor				
Charger Efficiency	90%				
Display	On-board LED				
Battery Type	Specific to selected Algorithm				
Operating Temperature	-30°C to +50°C				
Battery Connection	12 AWG Wire				
Dimensions (H x W x L)	110 x 246 x 280 mm				
Weight	5 Kg				
Warranty	2 Years				
Regulatory Compliance	Safety UL2202, UL1564 2nd Edition, CSA-C22.2 No. 107.2 EN60335-1/2-29 Emissions FCC Part 15 / ICES 003 Class A, EN55011 EN61000-3-2, EN61000-3-3 Immunity EN61000-4-2/-3/-4/-5/-6/-11				